





Pearl Wall Top Assemblies

Nero



Versions:202506

Top/Back



Specifications

Watermark License
WM-060073
Temperature Rating
Min 1°C-Max 75°C
Pressure Rating
Min 150kpa - Max 500kpa

Packaging Includes

2x Handwheels
1x Allen Key

Finish & SKU

 **Chrome**
NR201709CH  **Gun Metal**
NR201709GM

*Dimensions are nominal measurements only.

1

cap*2

grub screw*2

handle wheel*2

adapter*2

lock flange*2

lock nut*2

washer*2

quick-opening valve*2

ø44.4

ø49.5

50

75

ø35

G5/8

15-25

38-48

23

ceramic tile

wall

standard tap seat body

Install standard tap seat body as the dimension.

2

ceramic tile

wall

standard tap seat body

lock nut

washer

quick-opening valve

1.Screw the quick-opening valve onto the body tightly.

2.Put on the washer and screw the lock nut on the quick-opening valve.

3

ceramic tile

wall

lock flange

Screw lock flange tightly on the lock nut.

4

ceramic tile

wall

gauge

Screw gauge tightly on the lock nut.

5

ceramic tile

wall

cut off remaining thread

1.Cut off remaining thread against to the cut off gauge.

2. Use a file to make the cutting surface flat and smooth.

6

ceramic tile

wall

screw

adapter

1.Take off the cut off gauge.

2.Put on the adapter.

3.Fasten the screw firmly.

7

cap

ceramic tile

wall

grub screw

handle wheel

1.Put on handle wheel.

2.Fasten grub screw firmly.

3.Put cap back on handle wheel.

Nero

